VISUAL GUIDE TO LUTHERIE & ACOUSTICS

The Secret of the Violin's Soundpost

What it is, what it does, where it comes from, and how a luthier sets it blind through an opening barely 6 millimeters wide.

HISTORY · PHYSICS · TOOLS · STEP BY STEP · FIRST AID

Pedro Alfonso · Violinist · Composer · Communicator pedroalfonso.com

CHAPTER 01 · WHAT IS THE SOUNDPOST? — The Invisible Piece That Decides Everything

Inside every violin stands a small cylinder of spruce wood, barely 6 millimeters in diameter, wedged upright between the top plate and the back plate of the instrument. It uses no glue and no nails: it stays in place solely through the pressure of the strings and a millimeter-exact fit. That piece is the **soundpost**.

In Spanish, Italian, and French it is literally called the "soul" (*alma*, *anima*, *âme*) because it gives the violin its voice, projection, and character. From the outside it is invisible; on the inside it changes everything. With a properly fitted soundpost, the violin sings. With a poorly set one, it sounds dull, harsh, or unbalanced.




FIG. 1 · VIOLIN X-RAY. The bass bar runs lengthwise beneath the bass strings; the soundpost stands behind the treble foot of the bridge.

LANGUAGE	ONE PIECE, FIVE NAMES
Spanish	*alma* (soul)
Italian	*anima* (soul)
French	*âme* (soul)

LANGUAGE	ONE PIECE, FIVE NAMES
English	*soundpost*
German	*Stimmstock* (tuning stick)

SOUNDPOST BY THE NUMBERS (4/4 VIOLIN)			
6 mm	**~50 mm**	**8–10 kg**	**0**
diameter	height (varies by violin)	string pressure on bridge	drops of glue

Approximate measurements for a full-size (4/4) violin; every instrument has its own exact dimensions.

CHAPTER 02 · ANATOMY — Where the Soundpost Lives

From the outside, a violin looks perfectly symmetrical. On the inside, it is deliberately asymmetrical—and that is its acoustic engine.




FIG. 2 · CROSS-SECTION AT THE BRIDGE. Internal asymmetry turns string vibration into acoustic projection.

1. **Extreme load without glue:** Tuned strings exert roughly 20–22 kg of total tension and about 8–10 kg of vertical pressure on the bridge. Held purely by friction, the soundpost prevents the top plate (only 2.5 to 3 mm thick) from sinking over time.

2. **Pivot and piston:** The soundpost sits beneath the right foot of the bridge and the bass bar beneath the left. The right foot stays nearly fixed as a pivot; the left rises and falls like a piston, pumping air inside the body.

3. **The mistake of centering it:** If placed right on the centerline, it would lock the bridge's rocking motion and cancel the pumping of the top plate: the violin would lose projection and harmonic richness.

4. **Grain direction:** It is carved from straight, tight-grained spruce and installed with its grain running perpendicular to the grain of the top plate. Running parallel, it could act like a wedge and split the top.

CHAPTER 03 · WHAT IT DOES — Four Jobs in a Single Piece




FIG. 3 · ACOUSTIC ENGINE. The bridge rocks over the soundpost pivot while transferring energy directly into the maple back.

1. **Supports:** Absorbs part of the downward pressure coming through the bridge and protects the very thin top plate.

2. **Transmits:** Connects the top plate to the back plate—vibrations travel through the soundpost so the maple back radiates sound as well.

3. **Balances:** By anchoring one side of the bridge, it governs how the bridge rocks and distributes energy between bass and treble.

4. **Shapes character:** Moving it half a millimeter changes brightness, warmth, volume, and response under the bow.

WITHOUT A SOUNDPOST (OR POORLY SET)	WITH A PROPERLY SET SOUNDPOST
Dull sound with no projection	Clear voice with projection and character
Uneven strings: some loud, others weak	All four strings sound balanced
Sluggish response under the bow	Immediate response, even in *pianissimo*
Risk of the top plate sinking or cracking	Top plate works safely protected

It is the smallest and most powerful tone regulator in the entire instrument. A movement of half a millimeter can be heard.

CHAPTER 04 · HISTORY — Where the Soundpost Comes From

A piece as old as the violin itself, fine-tuned by hand across generations of luthiers.

ERA	MILESTONE
16th Century ***Cremona, Italy***	**The violin is born in northern Italy.** Around the first half of the 16th century, the violin family emerges in Italy. Andrea Amati (c. 1505–1577) of Cremona is considered the father of the classical violin tradition. From his earliest instruments, the soundpost is part of the interior design.
17th–18th Centuries	**The Golden Age of Cremona.** With Antonio Stradivari (c. 1644–1737) and Guarneri del Gesù (1698–1744), the craft reaches its summit. Every soundpost was hand-cut to fit its specific violin and adjusted by listening to the instrument.
19th Century	**Physics enters the workshop.** French physicist Félix Savart (1791–1841) systematically studies violin acoustics. As concert halls grow larger, older violins are adapted for higher string tension—reinforced bass bar and steeper neck angle. Soundpost adjustment becomes even more decisive.
20th Century	**Science measures what the ear already knew.** Researchers such as Frederick Saunders and Carleen Hutchins, and later Lothar Cremer, use laboratory instruments to study how the violin vibrates and what role the soundpost plays between top and back.
Today	**Same spruce, same idea.** Five centuries later, the soundpost is still a spruce cylinder, glue-free, hand-fitted by a luthier. Today it is studied with microphones and laser vibrometry—yet it is still set blind through an f-hole.

Approximate dates: records of the earliest luthiers are scarce, and historical attributions continue to be studied.

CHAPTER 05 · TOOLS — The Luthier's Tools

A closed violin is never opened just to adjust the soundpost. Everything is done through the right f-hole, which measures barely 6 to 8 mm at its widest point.



FIG. 4 · SOUNDPOST SETTER. A thin steel or brass blade whose S-curve clears the delicate edge of the f-hole.

TOOL	FUNCTION IN THE WORKSHOP
1. Soundpost Setter	The spear tip is pushed 2–3 mm into the side of the soundpost to hold it, enter through the f-hole, and stand it upright. The notched end (a concave push notch and a pull hook) nudges it half a millimeter at a time.
2. Mirror & Cool LED Light	A small long-handled mirror (like a dentist's mirror) and a cool LED light inserted through the left f-hole. They verify that the post stands completely plumb and makes 100% flush contact with both plates.
3. Soundpost Gauge	A small graduated ruler (40–70 mm). It measures the exact internal height before cutting the spruce and checks the post's distance behind the treble bridge foot.

Also used: spruce dowel blanks for carving custom soundposts and a sharp knife for beveling both ends.

CHAPTER 06 · STEP BY STEP — Blind Surgery (Steps 1 to 6)

Setting a soundpost is not merely standing it upright inside the box: the luthier follows a precise six-step protocol.




FIG. 5 · BLIND SURGERY (STEPS 1–3). Preparing the bevel, spearing the post with perpendicular grain, and clearing the right f-hole.

01. Measure the height and bevel both ends: The interior is not flat—top and back are arched. If cut straight at 90°, the post would touch only two corners and dent the wood. The luthier measures the exact internal height (50 to 55 mm on a 4/4) and carves a subtle bevel on both ends matching the arch angle.

02. Spear the soundpost onto the setter: Push the sharp tip 2 to 3 mm into the side of the cylinder, one-third down from its top end. Before spearing it, check the grain: its lines must sit perpendicular to the grain of the top plate.

03. Enter through the right f-hole without touching the edges: With the strings loosened, guide the cylinder through the widest part of the right f-hole (E-string side). This demands a steady hand: bumping the edge can splinter the spruce or scar the varnish.




FIG. 6 · BLIND SURGERY (STEPS 4–6). Standing the post upright, verifying flush contact with mirror and light, and dialing in tone by half-millimeters.

04. Stand it upright and release the tool: Once inside, the luthier turns the wrist to stand the cylinder upright between back and top, sliding it until it grips by light friction behind the treble foot of the bridge. A clean twist withdraws the metal spear, leaving the post standing.

05. Internal inspection with mirror and light: Using cool LED light, the luthier looks through the left f-hole with the mirror to verify two things: that the post stands completely plumb (no tilt forward or sideways) and that no light passes between its ends and the plates—100% contact.

06. Final acoustic adjustment—the magic of the millimeter: The bridge is set, the strings are tuned, and the violin is played. Using the notched end, the luthier gives tiny taps at the top and bottom of the post, 0.5 mm at a time, until all four strings sound balanced with crisp response and projection.

CHAPTER 07 · FINE ADJUSTMENT — One Millimeter Changes the Sound

Moving the soundpost half a millimeter alters the tension of the top plate and the harmonic balance of the entire instrument.




FIG. 7 · THE FOUR ADJUSTMENT AXES. Every direction shifts the balance between projection, warmth, bass, and treble.

DIRECTION	ACOUSTIC EFFECT	IF OVERDONE
Closer to the bridge	More projection, brightness, and attack; direct, focused sound.	Stiff, metallic, strident violin; *pianissimo* becomes hard to play.
Farther from the bridge	Warmer, darker, more open sound; easy response under the bow.	Loses volume, focus, and definition; hollow or weak treble.
Toward the center	Reinforces the bass strings (G and D); rounder, deeper timbre.	Too close to the centerline: chokes vibration and robs power from the highs.
Toward the f-hole	Boosts the treble strings (A and E) and clarifies articulation in the upper register.	Bass loses body; sound can become thin or nasal.

Starting point: a few millimeters behind the right foot of the bridge. The exact spot is unique to every violin—the luthier's ear decides.

CHAPTER 08 · WHO SETS IT — The Luthier: Surgeon of Wood




FIG. 8 · THE LUTHIER'S BENCH. Five simple tools guided by years of ear training and tactile precision.

Who they are. A luthier is someone who builds, repairs, and adjusts stringed instruments; the word comes from "lute." Setting a soundpost requires understanding wood, acoustics, and above all having trained hands and ears.

How they train. Through years of workshop apprenticeship and traditional schools such as Cremona (Italy) or Mittenwald (Germany). A great soundpost adjustment is one of the true signatures of the craft.

How long it takes. A checkup or adjustment may take only minutes; what stands behind it is years of practice.

When to go. Once a year, during seasonal weather changes, after a sharp knock to your case, or whenever you notice the sound change without explanation.

What to ask for. Ask them to check the position and fit of the soundpost, and tell them what you want—more brightness, more warmth, quicker response. They move the post millimeter by millimeter while listening.

> **! DO NOT TRY THIS AT HOME**
>
> Poking the soundpost with tweezers, pencils, or wires is the #1 cause of dented f-holes and internal cracks that later require expensive repairs. Leave this surgery in professional hands.

CHAPTER 09 · FIRST AID — If Your Soundpost Falls

That unmistakable *clack-clack* of loose wood rolling inside the violin. Stay calm—follow this protocol.

WARNING SIGN	WHAT YOU NOTICE
Clack-clack	The sound of loose wood rolling around when you tilt the violin.
Dull sound	Suddenly weak, lacking focus and projection.
Restless bridge	Sometimes the bridge tilts or the strings feel different under your fingers.

Emergency Protocol — Do This Immediately

1. **Loosen all four strings immediately:** You do not need to remove them, just release all tension. With tuned strings and no soundpost, up to 10 kg of pressure bears down on an unsupported top plate and can crack it.

2. **Remove the bridge carefully:** Once the strings are slack, the bridge comes loose. Take it off and store it separately in your case compartment so it does not knock against or scratch the varnish.

3. **Do NOT shake the violin to get it out:** Trying to shake the soundpost out through the f-hole often splinters the edges or slams into the bass bar. Leave it inside while transporting the violin.

4. **Do NOT try to stand it up with tweezers, pencils, or wires:** This is the most common cause of f-hole dents and internal cracks that later require costly repairs.

5. **Take it to a professional luthier:** If the soundpost was not damaged, resetting and adjusting it is usually a quick and affordable procedure.

Prevention

- Change strings one at a time—never all four at once.
- Keep humidity stable (40–60%).
- Avoid hard jolts to the case and sudden climate swings.
- Schedule an annual checkup with your luthier.

CHAPTER 10 · IN 10 SECONDS — The Essentials

Everything you need to keep with you.

#	TOPIC	KEY TAKEAWAY
1	**What it is**	A 6 mm spruce cylinder standing upright between top and back, with zero glue.
2	**Where it goes**	Behind the right foot of the bridge (A–E side), never in the center.
3	**What it does**	Supports the top, transmits vibration to the back, balances the strings, and gives character.
4	**Who sets it**	A luthier, using an S-curved setter, mirror, cool LED light, and gauge.
5	**If it falls**	Loosen the strings, remove the bridge, don't shake it out, and visit a luthier.
6	**To prevent it**	Change strings one by one and protect against humidity swings.

Quick Questions

QUESTION	ANSWER
Can the soundpost be glued?	No—it stays free so the luthier can adjust and move it.
How often should it be checked?	Once a year, or as soon as you notice an unusual change in sound.
Can I move it myself?	No. Half a millimeter changes the sound, and one slip can damage your violin.

Found this guide helpful? Save it on your phone or share it with a fellow violinist before they change all four strings at once. If your soundpost has ever fallen or you have questions about your instrument, send me a DM and let's talk.

Pedro Alfonso *· Violinist, Composer & Communicator · pedroalfonso.com*